Features

- Ultra Stable
- Wide Temperature Range
- SMD Package (7.0×5.0mm)
- Provide Stratum Ⅲ Level Frequency Stability

Applications

- Base Stations
- Instrumentations
- Synthesizer
- SDH/SONET
- Medical Electronics

BT0507A&B Specifications

Parameter		Value			Unit	Conditions	
		Min.	Typ.	Max.			
Supply Voltage		–	3.3	–	V	Vcc±5%	
		–	5	–	V	Vcc±5%	
Supply Current		–	–	10	mA	10MHz~26MHz (Including 26MHz)	
		–	–	20	mA	26MHz~60MHz	
Frequency Range		10 ~ 52			MHz		
Nominal Frequency		10, 12.8, 16, 16.384, 19.2, 20, 24.576, 25, 26, 30.72, 40, 50			MHz		
Initial Frequency Tolerance		±0.3	–	±0.5	ppm	At shipment, nominal EFC, +25°C	
Freq. Stability Vs. Temp.		±0.05	–	±0.5	ppm	-20°C~+70°C	
		±0.05	–	±0.5	ppm	-40°C～+85°C	
		±0.2	–	±1.0	ppm	-50°C～+90°C except for 10MHz	
		±0.5	–	±1.0	ppm	-55°C～+95°C except for 10MHz	
Clipped Sine Wave	Output Level	0.8	–	–	Vp-p		
	Load	10kΩ//10pF					
HCMOS	V_{OH}	2.4	–	–	V	HCMOS Output, Load=15pf	
	V_{OL}	–	–	0.4	V	HCMOS Output, Load=15pf	
	Duty Cycle	45	–	55	%	(V_{OH} - V_{OL})/2	
	Rise/Fall Edge	–	–	6	ns	HCMOS Output, Load=15pf	
	Load	–	–	15	pf		
RMS Jitter(By E5052B)		0.4	–	1.3	ps	12KHz~5MHz	
Supply Sensitivity		–	–	±0.1	ppm	Vcc±5%	
Load Sensitivity		–	–	±0.2		Load±5%	
Aging/ First Year		–	–	±1.0		Standard	
SSB Phase Noise @10MHz		–	–	-95	dBc/Hz	Offset 10Hz	At +25°C
		–	–	-120		Offset 100Hz	
		–	–	-140		Offset 1kHz	
		–	–	-145		Offset 10kHz	
		–	–	-150		Offset 100kHz	
Control Voltage Range		1.5 ± 1.0			V		
Frequency Tuning Range		±5	–	±12	ppm		
Tuning Slope		positive					
Non-linearity		–	–	10	%		

Phase Noise @1KHz

Frequency Range	<-125dBc	<-130dBc	<-135dBc	<-140dBc	
10MHz	○	○	○	○	○=Available X= Not Available
12.8MHz~20MHz	○	○	○	X	
20.48MHz~38.4MHz	○	○	X	X	
⩾40MHz	○	X	X	X	

Environmental Conditions

Operating Temperature Range	-55°C～+95°C
Storage Temperature Range	-55°C ~ +125°C

Outline Dimension & Pin Connections

BT0507A



Pin Connections

#1	NC / Vcont
#2	GND
#3	Output
#4	Vcc

unit : mm
Dimensional Tolerance : ±0.3

Recommended Land Pattern



BT0507E



Pin Connections

#1	NC / Vcont
#2	GND
#3	Output
#4	Vcc

unit : mm
Dimensional Tolerance : ±0.3

Recommended Land Pattern



Note:
1. The pins with '*' are for factory test.
2. Leave pin 1 unconnected If Vcon is not used.

Maximum Ratings

Parameter	Symbol	Rating
Supply Voltage	Vdd	-0.5V / 6V
Control Voltage	Vcon	0V / 3V
ESD, HBM/CDM/MM		4KV/ 2KV/ 200V

Reliability

Parameter	Condition
Temperature Stress Test	IEC60068, GJB360B
Mechanical Stress Test	IEC60068, GJB360B
EMC Test (ESD)	IEC61000, JESD22
Solderability	EIA/JESD22-B102-C
Moisture sensitivity Level	MSL3
Bonding pad	Gold over Nickel
RoHS	RoHS Directive 2011/65/EU Annex II Recasting 2002/95/EC

Ordering Guide

BT 0507 X X X X XXX X X XX.XX

- Product: TCXO
- Outline: 7.0mm x 5.0mm
- Package: A: Pakcage A; B: package B
- Output: H: CMOS; C: Clipped Sine Wave
- Supply Voltage: 3: 3.3 Vdc; 5: 5.0 Vdc
- Temp. Range: C: -20℃ ~ +70℃; I: -40℃ ~ +85℃; M: -50℃ ~ +90℃; U: -55℃ ~ +95℃; F: Customized
- Temp. Stability: 106: ±1.0ppm; 507: ±0.5ppm; 207: ±0.2ppm; 107: ±0.1ppm; 508: ±0.05ppm
- Phase Noise: A: -120dBc/Hz@1kHz; B: -125dBc/Hz@1kHz; C: -130dBc/Hz@1kHz; D: -135dBc/Hz@1kHz; E: -140dBc/Hz@1kHz
- Tuning Range: N:No Tuning; A: ±5ppm; B: ±7ppm; C: ±12ppm
- Frequency: xx MHz

Example: BT0507BH3M287DN16.384

Reflow Profile



Disclaimer

Xtaltq Technologies Co., Limited reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.